


1. ALL SIGNAL HEADS SHALL BE 12" DIA. AND SHALL BE MOUNTED ON 4" DIA. PIPES.
 2. ALL SIGNAL HEADS SHALL BE EQUIPPED WITH 24" DIA. MOUNTS.
 3. ALL SIGNAL HEADS SHALL BE EQUIPPED WITH 24" DIA. MOUNTS.



PREFERENTIAL PHASE SEQUENCE

- CONSTRUCTION NOTES:
1. ALL SIGNAL HEADS SHALL BE 12" DIA. AND SHALL BE MOUNTED ON 4" DIA. PIPES.
 2. ALL SIGNAL HEADS SHALL BE EQUIPPED WITH 24" DIA. MOUNTS.
 3. ALL SIGNAL HEADS SHALL BE EQUIPPED WITH 24" DIA. MOUNTS.
 4. ALL SIGNAL HEADS SHALL BE EQUIPPED WITH 24" DIA. MOUNTS.
 5. ALL SIGNAL HEADS SHALL BE EQUIPPED WITH 24" DIA. MOUNTS.
 6. ALL SIGNAL HEADS SHALL BE EQUIPPED WITH 24" DIA. MOUNTS.
 7. ALL SIGNAL HEADS SHALL BE EQUIPPED WITH 24" DIA. MOUNTS.
 8. ALL SIGNAL HEADS SHALL BE EQUIPPED WITH 24" DIA. MOUNTS.
 9. ALL SIGNAL HEADS SHALL BE EQUIPPED WITH 24" DIA. MOUNTS.
 10. ALL SIGNAL HEADS SHALL BE EQUIPPED WITH 24" DIA. MOUNTS.